

## Double Row Angular Contact Ball Bearing



Bearing Number			Principal dimensions				Basic load ratings		Speed ratings		Weight
open	shielded	seals	d	D	B	r(min)	dynamic(Cr)	static(Cor)	grease	oil	weight
3200	ZZ	2RS	10	30	14.3	0.6	7420	4300	16333	22000	0.054
3201	ZZ	2RS	12	32	15.9	0.6	10200	5600	15000	20000	0.058
3202	ZZ	2RS	15	35	15.9	0.6	11200	6800	12000	17000	0.066
3302	ZZ	2RS		42	19	0.6	15100	9150	10000	15000	0.13
3203	ZZ	2RS	17	40	17.5	0.6	14000	8650	10000	15000	0.1
3303	ZZ	2RS		47	22.2	0.6	21200	12500	9500	14000	0.18
3204	ZZ	2RS	20	47	20.6	1	18500	12000	9000	13000	0.16
3304	ZZ	2RS		52	22.2	1.1	22200	14200	8500	12000	0.22
3205	ZZ	2RS	25	52	20.6	1	20200	14000	8000	11000	0.18
3305	ZZ	2RS		62	25.4	1.1	31200	20800	7500	10000	0.35
3206	ZZ	2RS	30	62	23.8	1	25200	20000	7000	9500	0.29
3306	ZZ	2RS		72	30.2	1.1	36800	28500	6300	8500	0.53
3207	ZZ	2RS	35	72	27	1.1	33500	27500	6000	8000	0.44
3307	ZZ	2RS		80	30.2	1.1	36800	28500	6300	8500	0.53
3208	ZZ	2RS	40	80	30.2	1.1	40500	33500	5600	7500	0.58
3308	ZZ	2RS		90	36.5	1.5	53200	43000	5000	6700	0.95
3209	ZZ	2RS	45	85	30.2	1.1	42800	38000	5000	6700	0.63
3309	ZZ	2RS		100	39.7	1.5	64800	73500	4500	6000	1.4
3210	ZZ	2RS	50	90	30.2	1.1	42800	39000	4800	6300	0.66
3310	ZZ	2RS		110	44.4	2	79200	96500	4000	5300	1.95
3211	ZZ	2RS	55	100	33.3	1.5	51500	67000	4300	5600	1.05
3311	ZZ	2RS		120	49.2	2	85800	108000	3800	5000	2.55
3212	ZZ	2RS	60	110	36.5	1.5	65000	85000	3800	5000	1.4

### Double Row Angular Contact Ball Bearing

3312	ZZ	2RS		130	54	2.1	100000	128000	3400	4500	3.25	
3213	ZZ	2RS	65	120	38.1	1.5	70200	9500	3600	4800	1.75	
3313	ZZ	2RS		140	58.7	2.1	115000	150000	3200	4300	4.1	
3214	ZZ	2RS	70	125	39.7	1.5	68800	98000	3200	4300	1.9	
3314	ZZ	2RS		150	63.5	2.1	132000	172000	2800	3800	5.05	
3215	ZZ	2RS	75	130	41.3	1.5	75800	110000	3200	4300	2.1	
3315	ZZ	2RS		160	68.3	2.1	142000	185000	2600	3600	6.15	