


Rod End



Bearing number	Dimensions(mm)								Load ratings KN		≈a° Weight	
	d	B	dk	C1 max	d2	D3 6H	h1	I4	Dynamic	Static		kg
SI5T/K	5	8	11.11	7.5	18	M5X0.8	27	36	3.6	4.6	4	0.02
SI6T/K	6	9	12.7	7.5	20	M6X1	30	40	4.7	5.2	9	0.025
SI8T/K	8	12	15.8	9.5	24	M8X1.25	36	48	7.6	8.2	12	0.047
SI10T/K	10	14	19.05	11.5		M10X1.5	43	58	12	15	10	0.088
SI10T/K	10	14	19.05	11.5		M10X1.25	43	58	12	15	10	0.088
SI12T/K	12	16	22.23	12.5		M12X1.75	50	67	14	19	12	0.14
SI12T/K	12	16	22.23	12.5		M12X1.25	50	67	14	19	12	0.14
S114T/K	14	19	25.4	14.5		M14X2	57	76	19	24	14	0.2
S114T/K	14	19	25.4	14.5		M14X1.5	57	76	19	24	14	0.2
S16T/K	16	21	28.58	15.5		M16X2	64	85	23	29	14	0.25
S16T/K	16	21	28.58	15.5		M16X1.5	64	85	23	29	14	0.25
SI18T/K	18	23	31.75	17.5	46	M18X1.5	71	94	29	34	15	0.35
SI20T/K	20	25	34.93	18.5	50	M20X1.5	77	102	34	40	14	0.43
SI22T/K	22	28	38.1	21	54	M22X1.5	84	112	42	50	14	0.61
SI25T/K	25	31	42.86	23	60	M24X2	94	124	52	57	14	0.81
SI30T/K	30	37	50.8	27	70	M30X2	110	145	73	77	17	1.4
SI35T/K	35	43	57.15	28	80	M36X2	125	165	110	116	17	1.6
SA5T/K	5	8	11.11	7.5	18	M5X0.8	33	42	3.6	3.9	4	0.013
SA6T/K	6	9	12.7	7.5	20	M6X1	36	46	4.7	5.2	9	0.02
SA8T/K	8	12	15.8	9.5	24	M8X1.25	42	54	7.6	8.2	12	0.038
SA10T/K	10	14	19.05	11.5	28	M10X1.5	48	63	12	15	12	0.071

Rod End

SA10T/K	10	14	19.05	11.5	28	M10X1.25	48	63	12	15	12	0.071	
SA12T/K	12	16	22.23	12.5	32	M12X1.75	54	71	14	19	12	0.12	
SA12T/K	12	16	22.23	12.5	32	M12X1.25	54	71	14	19	12	0.12	
SA14T/K	14	19	25.4	14.5	36	M14X2	60	79	19	24	14	0.17	
SA14T/K	14	19	25.4	14.5	36	M14X1.5	60	79	19	24	14	0.17	
SA16T/K	16	21	28.58	15.5	42	M16X2	66	87	23	29	14	0.23	
SA16T/K	16	21	28.58	15.5	42	M16X1.5	66	87	23	29	14	0.23	
SA18T/K	18	23	31.75	17.5	46	M18X1.5	72	95	29	34	13	0.31	
SA20T/K	20	25	34.93	18.5	50	M20X1.5	78	103	34	40	14	0.4	