

Self-Aligning Ball Bearing



Bearing Number		Principal dimensions				Basic load ratings		Speed ratings		Weight
cylindrical bore	Tapered Bore	d	D	B	r(min)	dynamic(Cr)	static(Cor)	grease	oil	weght
135	-	5	19	6	0.3	2510	480	28000	34000	0.009
126	-	6	19	6	0.3	2510	480	28000	34000	0.009
127	-	7	22	7	0.3	2650	560	26000	36000	0.014
108	-	8	22	7	0.3	2650	560	26000	36000	0.014
129	-	9	26	8	0.6	3900	815	24000	28000	0.021
1200	1200K	10	30	9	0.6	5480	1200	24000	28000	0.035
2200	2200K	10	30	14	0.6	7120	1580	24000	28000	0.05
1300	1300K	10	35	11	0.6	7220	1620	20000	24000	0.06
2300	2300K	10	35	17	0.6	11000	2450	18000	22000	0.09
1201	1201K	12	32	10	0.6	5550	1250	22000	26000	0.042
2201	2201K	12	32	14	0.6	8800	1800	22000	26000	0.053
1301	1301K	12	37	12	1	9420	2120	18000	22000	0.07
2301	2301K	12	37	17	1	12500	2720	17000	22000	0.095
1202	1202K	15	35	11	0.6	7480	1750	18000	22000	0.051
2202	2202K	15	35	14	0.6	7650	1800	18000	22000	0.06
1302	1302K	15	42	13	1	9500	2280	16000	20000	0.1
2302	2302K	15	42	17	1	12000	2880	14000	18000	0.11
1203	1203K	17	40	12	0.6	7900	2020	16000	20000	0.076
2203	2203K	17	40	16	0.6	9000	2450	16000	20000	0.09
1303	1303K	17	47	14	1	12500	3180	14000	17000	0.14
2303	2303K	17	47	19	1	14500	3580	13000	16000	0.17

Self-Aligning Ball Bearing

1204	1204K	20	47	14	1	9950	2650	14000	17000	0.12
2204	2204K	20	47	18	1	12500	3280	14000	17000	0.15
1304	1304K	20	52	15	1.1	12500	3380	12000	15000	0.17
2304	2304K	20	52	21	1.1	17800	4750	11000	14000	0.22
1205	1205K	25	52	15	1	12000	3330	12000	14000	0.14
2205	2205K	25	52	18	1	12500	3400	12000	14000	0.19
1305	1305K	25	62	17	1.1	17800	5050	10000	13000	0.26
2305	2305K	25	62	24	1.1	24500	6480	9500	12000	0.35
1206	1206K	30	62	16	1	15800	4700	10000	12000	0.23