

Single Row Angular Contact Ball Bearing



Bearing Number	Principal dimensions					Basic load ratings		Speed ratings		weight weight(kg)
	d	D	B	B1	r(min)	dynamic(Cr)	static(Cor)	grease	oil	
7000C	10	26	8	0.3	0.15	4920	2250	19000	28000	0.018
7000AC	10	26	8	0.3	0.15	4750	2120	19000	28000	0.018
7200C	10	30	9	0.6	0.3	5820	2950	18000	26000	0.03
7200AC	10	30	9	0.6	0.3	5580	2820	18000	26000	0.03
7200B	10	30	9	0.6	0.3	5580	2820	18000	26000	0.03
7001C	12	28	8	0.3	0.15	5420	2650	18000	26000	0.02
7001AC	12	28	8	0.3	0.15	5200	2550	18000	26000	0.02
7201C	12	32	10	0.6	0.3	7350	3520	17000	24000	0.035
7201AC	12	32	10	0.6	0.3	7100	3350	17000	24000	0.035
7201B	12	32	10	0.6	0.3	7100	3300	17000	24000	0.035
7301B	12	37	12	0.6	0.3	9600	4000	16000	22000	0.06
7002C	15	32	9	0.3	0.15	6250	3420	17000	24000	0.028
7002AC	15	32	9	0.3	0.15	5950	3250	17000	24000	0.028
7202C	15	35	11	0.6	0.3	8680	4620	16000	22000	0.043
7202AC	15	35	11	0.6	0.3	8350	4400	16000	22000	0.043
7202B	15	35	11	0.6	0.3	8300	4300	16000	22000	0.043
7302B	15	42	13	1	0.6	12000	6000	14000	19000	0.08
7003C	17	35	10	0.3	0.15	6600	3850	16000	22000	0.036
7003AC	17	35	10	0.3	0.15	6300	3680	16000	22000	0.036
7203C	17	40	12	0.6	0.3	10800	5950	15000	20000	0.062
7203AC	17	40	12	0.6	0.3	10500	5650	15000	20000	0.062
7203B	17	40	12	0.6	0.3	9950	5500	14000	19000	0.062

Single Row Angular Contact Ball Bearing

7303B	17	47	14	1	0.6	14000	8000	13000	18000	0.11	
7004C	20	42	12	0.6	0.3	10500	6080	14000	19000	0.064	
7004AC	20	42	12	0.6	0.3	10000	5780	14000	19000	0.064	
7204C	20	47	14	1	0.6	14500	8220	13000	18000	0.1	
7204AC	20	47	14	1	0.6	14000	7820	13000	18000	0.1	
7204B	20	47	14	1	0.6	14000	7850	13000	18000	0.11	
7304B	20	52	15	1	0.6	17300	9650	1100	15000	0.14	
7005C	25	47	12	0.6	0.3	11500	7450	12000	17000	0.074	